



Specification Statements FSH Products

1. Electric Door Strike FES15 Rim-Mount, non monitored

"The rim-mounted, non monitored electric door strike must be equal to the FSH model FES15 in all respects. It must accept voltages of either 12 or 24VDC, be fire tested up to a 2 hour fire resistance rating to both Australian and British Fire Test Standards and weather resistant IP56 as a standard. The strike must be easily site-interchangeable power to lock (PTL) or power to release (PTR) by simply removing the security cap and changing over the Barbell mechanism. The device must be provided with a 5 year warranty and has to have a holding strength of up to 1250kg."

Product features

- Barbell mechanism for easy change of locking function
- Low power consumption
- Weather resistant IP56
- Superior holding strength of up to 1250kg
- 5 year warranty
- 12 or 24VDC operation
- Surface mount for RIM-Locks

2. Electric Door Strike FES15M Rim-Mount, monitored

"The rim-mounted, non monitored electric door strike must be equal to the FSH model FES15 in all respects. It must accept voltages of either 12 or 24VDC and be fire tested up to a 2 hour fire resistance rating to both Australian and British Fire Test Standards. The strike must be easily site-interchangeable power to lock (PTL) or power to release (PTR) by simply removing the security cap and changing over the Barbell mechanism. The device must be provided with a 5 year warranty and has to have a holding strength of up to 1250kg. The door strike must provide door latch monitoring within the strike keeper as well as Anti-Tamper-Monitoring of the strike itself.

Product features

- Barbell mechanism for easy change of locking function
- Low power consumption
- Superior holding strength of up to 1250kg
- 5 year warranty
- 12 or 24VDC operation
- Surface mount for RIM-Locks
- Anti-Tamper Monitoring of the strike itself and door latch monitoring